

## ELEKTRISCH

Input	3 x 400VAC + N 230VAC
Daisy chain	Nee
Frequentie	50 Hz
Beveiliging	/
Aantal laadpunten	2
Laadvermogen	<ul style="list-style-type: none"> <li>• 22 kW (3 x 400VAC + N – 32A)</li> <li>• 11 kW (3 x 400VAC + N – 16A)</li> <li>• 7,4 kW (230VAC – 32A)</li> <li>• 3,7 kW (230VAC – 16A)</li> </ul>
Laadmode	Mode 3 per IEC61851
Energiemeter	/

## MECHANISCH

Afmetingen (H x B x D)	1400 mm x 193,7 mm x 193,7 mm
Gewicht	± 40 kg
IP	IP54
IK	IK10
Materiaal	Staal S235
Beschikbare kleuren	WH (RAL 9016) / BK (RAL 9005) GY (AKZO 900) / CM (CUSTOM MADE)
Type stekker	Type 2
Lengte laadkabel	5 meter

## STANDAARDEN

EV laadstandaarden	IEC 61851-1, IEC 61851-21-2
--------------------	-----------------------------

## COMMUNICATIE EN INTERFACES

Status indicatie	RGB LED
Activatie methode	Plug & charge , RFID
Communicatie interface	/
Communicatie protocol	/